



# BAS19 / BAS20 / BAS21

## Surface Mount Fast Switching Diode



Voltage Range  
100/150/200 Volts  
250m Watts Power Dissipation


### Features

- ✧ Fast switching speed
- ✧ Surface mount package ideally suited for automatic insertion
- ✧ For general purpose switching applications
- ✧ High conductance

### Mechanical Data

- ✧ Case: SOT-23, Molded plastic
- ✧ Terminals: Solderable per MIIIL-STD-202, Method 208
- ✧ Polarity: See diagram
- ✧ BAS19 Marking: A8
- ✧ BAS20 Marking: A81
- ✧ BAS21 Marking: A82
- ✧ Weight: 0.008 gram (approx.)

### SOT-23



Dimensions in inches and (millimeters)

### Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

#### Maximum Ratings

Type Number	Symbol	BAS19	BAS20	BAS21	Units
Repetitive Peak Reverse Voltage	VRRM	120	200	250	V
Working Peak Reverse Voltage DC Blocking Voltage	VRWM VR	100	150	200	V
RMS Reverse Voltage	VR(RMS)	71	106	141	V
Forward Continuous Current (Note 1)	IFM	400			mA
Average Rectifier Output Current (Note 1)	Io	200			mA
Non-Repetitive Peak Forward Surge Current @ t=1.0uS @ t=1.0S	IFSM	2.5 0.5			A
Repetitive Peak Forward Surge Current	IFRM	625			mA
Power Dissipation (Note 1)	Pd	250			mW
Thermal Resistance Junction to Ambient Air (Note 1)	R θ JA	500			K/W
Operating and Storage Temperature Range	TJ, TSTG	-65 to + 150			°C

#### Electrical Characteristics

Type Number	Symbol	Min	Max	Units
Forward Voltage IF=100mA IF= 200mA	VF	-	1.0 1.25	V
Peak Reverse Current Tj=25 °C Tj=100°C	IR	-	100 15	nA uA
Junction Capacitance VR=0, f=1.0MHz	Cj	-	5.0	pF
Reverse Recovery Time (Note 2)	ttr	-	50	nS

Notes: 1. Valid Provided that Terminals are Kept at Ambient Temperature.

2. Reverse Recovery Test Conditions: IF=IR=10mA, Irr=0.1 x IR, RL=100Ω.

## RATINGS AND CHARACTERISTIC CURVES (BAS19 THRU BAS21)

FIG.1- FORWARD CHARACTERISTICS





FIG.2- LEAKAGE CURRENT VS JUNCTION TEMPERATURE



[www.s-manuals.com](http://www.s-manuals.com)